

KOAXKABEL CU UND STACU INNENLEITER

					
Type	KK 2000	KK 2200	POKA 99 HD	KK 2300	KK 2120
Schirmungsmaß (db)	100	100	99	>110	120
Innenleiter / Aufbau	1,13 Cu	0,75 Cu	1,0 Cu	1,0 Cu	1,13 Cu
Isolation	4,8 PEE	4,5 PE	4,8 PEE	4,6 PEE	4,8 PEE
Schirmfolie	ALPR	ALPR	2xALPET	2xALPR	2xALPR
Schirmgeflecht	128x0,12	160x0,12	128x0,12	1x 96x0,12 Al / 1x 48x0,12 Al	1x 128x0,12 Al / 1x 96x0,12 Al
Mantel / Farbe	6,8 PVC weiß	6,7 PVC weiß	7,1 PVC weiß	7,4 PVC weiß	8,2 PVC weiß
Wellenwiderstand Ω (Ohm)	75 +/-3	75 +/-3	75 +/-3	75 +/-3	75 +/-3
Verkürzungsfaktor (v/c)	0,8	0,66	0,85	0,8	0,8
Dämpfung dB/100m (MHz)					
100	4,9	8,1	6,18	5,2	4,9
200	7,2	11,9	8,62	8,3	6,7
450	11,6	17,9	12,45	12,8	11,9
800	16,5	24,6	18,05	16,2	15,3
1000	16,5	28,2	20,48	19,8	17,4
1750	26,6	38,1	27,2	26,5	23,9
2050	28,2	41,9	30,8	30,2	27,3
2250	29,5	47,2	/	/	/
2500	31,9	/	/	/	/
Rückflußdämpfung (MHz)					
30-450	40	40	>21	40	45
450-900	40	30	>18	38	42
900-1600	35	27	>16	33	40
1600-2400	30	/	>16	70	80
Biegeradius (mm)	50	45	70	35	80

			
Type	KK 2050	KK 2450	KK 2550
Schirmungsmaß (db)	>110	>95	90
Innenleiter / Aufbau	1,1 StaCu	1,1 StaCu	1,13 StaCu
Isolation	4,8 PEE	4,8 PEE	4,8 PEE
Schirmfolie	2xALPR	ALPR	ALPR
Schirmgeflecht	128x0,12	128x0,12	128x0,12
Mantel / Farbe	7,2 PVC weiß	6,8 PVC weiß	6,8 PVC schwarz
Wellenwiderstand Ω (Ohm)	75	75	75
Verkürzungsfaktor (v/c)	0,8	0,8	0,8
Dämpfung dB/100m (MHz)			
100	5,1	5,1	5,7
200	6,9	6,9	7,9
450	12,2	12,2	12,3
800	15,6	15,6	17,6
1000	17,8	17,8	19,4
1750	24,4	24,4	26,9
2050	27,8	27,8	28,5
2250	/	/	29,8
2500	/	/	32,8
Rückflußdämpfung (MHz)			
5-1000	28	28	>30
1000-2000	24	24	>25
2000-3000	>20	>20	>22
Biegeradius (mm)	35	35	70